



# Optibay SV 6D



Public



Housing



Industrial



For railway stations  
and subways



For parking lots



Warehouse




Agricultural

DSTU EN 60598-1  
DSTU EN 60598-2-3

~100...305V  
47..63 Hz

IP

67



**Ledil**<sup>®</sup>  
strada 2x6<sup>™</sup>



## Technical characteristics of the luminaire

### General information:

Testing standard	DSTU EN 60598-1/DSTU EN 60598-2-3
Manufacturing without use of lead. Pb free	Yes

### Mechanical characteristics:

Coating material	Aluminum alloy AMg2
Optics material	Platic PC or Acrylic (PMMA)
Standard color	Black, grey, white or as per order
Degree of shell protection	IP67
Degree of protection against mechanical damage	IK08

### Environmental requirements:

Ambient temperature	-40 °C...+50 °C
---------------------	-----------------

### Electrical characteristics:

Class of protection against electric shock	Class I
Nominal power	180/230 W
Nominal supply voltage	~100-305 V 47-63 Hz
Power factor	>0,9
Electromagnetic compatibility	DSTU EN 55015/DSTU EN 61547/DSTU EN 61000-3-2/DSTU EN 61000-3-3

### Lighting information:

Color temperature	3000/4000/5000 K
Luminous flux (depending on power)	25920...32430 Lm
CRI color rendering index	≥ 70
Availability of pulsations	≤ 5%
Avg. service life of the luminaire	at least 100 000 hours
Type of optics	as per order

### Dimensions and weight:

Length x Width x Height	32.28 x 11.81 x 2.55 inch
Weight	13.22 lbs

### Mounting:

Mounting options	adjustable bracket, non-adjustable bracket, non-adjustable on the cable
------------------	---

### Optional:

Other	the presence of a casing
-------	--------------------------

